



CURRENT 10 Ampere  
 VOLTAGE RANG 600 Volts

## ASE10N60

### FEATURE


- 10A,600V, $R_{DS(ON)}=0.85\Omega @V_{GS}=10V/5A$
- Low gate charge
- Low  $C_{iss}$
- Fast switching
- 100% avalanche tested
- Improved dv/dt capability



TO-220AB  
10N60



ITO-220AB  
10N60F



TO-263  
10N60B



TO-262  
10N60H

Absolute Maximum Ratings ( $T_C=25^\circ\text{C}$ , unless otherwise noted)			
Parameter	Symbol	ASE10N60	UNIT
Drain-Source Voltage	$V_{DSS}$	600	V
Gate-Source Voltage	$V_{GSS}$	$\pm 30$	
Continuous Drain Current	$I_D$	10	A
Pulsed Drain Current (Note 1)	$I_{DM}$	40	
Single Pulse Avalanche Energy (Note 2)	$E_{AS}$	300	mJ
Avalanche Current (Note 1)	$I_{AR}$	10	A
Repetitive Avalanche Energy (Note 1)	$E_{AR}$	30	mJ
Reverse Diode dV/dt (Note 3)	dv/dt	5.5	V/ns
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to +150	$^\circ\text{C}$
Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	$T_L$	260	$^\circ\text{C}$
Mounting Torque	6-32 or M3 screw	10	lbf • in
		1.1	N • m

Thermal Characteristics					
Parameter	Symbol	ITO-220	TO-220	TO-262 TO-263	Units
Maximum Junction-to-Case	$R_{thJC}$	1.0	0.8	0.8	$^\circ\text{C}/\text{W}$
Maximum Power Dissipation	$P_D$	125	155	155	W

CURRENT 10 Ampere  
 VOLTAGE RANG 600 Volts

## ASE10N60

Electrical Characteristics ( $T_c=25^{\circ}\text{C}$ , unless otherwise noted)						
Parameter	Symbol	Test Conditions	Mix	Typ	Max	Units
<b>Off Characteristics</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu A$	600	—	—	V
Breakdown Temperature Coefficient	$\Delta BV_{DSS} / \Delta T_j$	Reference to $25^{\circ}\text{C}$ , $I_D=250\mu A$	—	0.6	—	$V/^{\circ}\text{C}$
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=600V, V_{GS}=0V$	—	—	1	$\mu A$
Gate-Body Leakage Current, Forward	$I_{GSSF}$	$V_{GS}=30V, V_{DS}=0V$	—	—	10	$\mu A$
Gate-Body Leakage Current, Reverse	$I_{GSSR}$	$V_{GS}=-30V, V_{DS}=0V$	—	—	-10	$\mu A$
<b>On Characteristics</b>						
Gate-Source Threshold Voltage	$V_{GS(th)}$	$V_{DS}=10V, I_D=250\mu A$	2	—	4	V
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=5A$	—	—	0.85	$\Omega$
<b>Dynamic Characteristics</b>						
Input Capacitance	$C_{iss}$	$V_{DS}=25V, V_{GS}=0V,$ $f=1.0\text{MHZ}$	—	—	1500	pF
Output Capacitance	$C_{oss}$		—	—	180	pF
Reverse Transfer Capacitance	$C_{rss}$		—	—	15	pF
<b>Switching Characteristics</b>						
Turn-On Delay Time	$t_{d(on)}$	$V_{DD}=300V, I_D=10A,$ $R_G=25\Omega$ (Note4,5)	—	20	—	ns
Turn-On Rise Time	$t_r$		—	20	—	ns
Turn-Off Delay Time	$t_{d(off)}$		—	55	—	ns
Turn-Off Fall Time	$t_f$		—	30	—	ns
Total Gate Charge	$Q_g$	$V_{DS}=480V, I_D=10A,$ $V_{GS}=10V,$ (Note4,5)	—	60	—	nC
Gate-Source Charge	$Q_{gs}$		—	12	—	nC
Gate-Drain Charge	$Q_{gd}$		—	28	—	nC
<b>Drain-Source Body Diode Characteristics and Maximum Ratings</b>						
Continuous Diode Forward Current	$I_S$		—	—	10	A
Pulsed Diode Forward Current	$I_{SM}$		—	—	40	A
Diode Forward Voltage	$V_{SD}$	$I_S=10A, V_{GS}=0V$	—	—	1.5	V
Reverse Recovery Time	$t_{rr}$	$V_{GS}=0V, I_S=10A,$ $dI_F/dt=100A/\mu s,$ (Note4)	—	600	—	ns
Reverse Recovery Charge	$Q_{rr}$		—	4.3	—	$\mu C$